

# PLUSVAC 25

## Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Lid locking can be unhooked
- Dynamic end position damping of the lid opening
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Convex plexiglas lid

## Selectable options

- Gas flushing (MAP)
- Program control with sensor (Perfect)
- Connection for external extraction (container)
- Cut-off and sealing
- Compressed air pressure sealing, external air compressor required
- Switch off sealing bar
- Bigger vacuum pumps
- Voltage variants
- ESD-Version
- Plug with phase inverter
- Higher lid

## Technical data

<b>Chamber size (w x l x h / mm)</b>	640 x 480 x 200 (250)
<b>Control board</b>	
• Standard	Comfort
• Option	Perfect
<b>Sealing length (mm)</b>	4 x 455
<b>Sealing seam</b>	double
<b>Distance x (mm)</b>	(540)
<b>Position of sealing bar</b>	
• Standard	right, left
• Option	right or left
<b>Pump (cbm/h)</b>	40 (60/106/151)
<b>Power connection</b>	400V/3Ph+N+PE/50Hz
<b>Power from (kW)</b>	2,1 (2,5/3,3/4,5)
<b>Max. bag (mm)</b>	450 x 600
<b>Insert plates</b>	3/chamber
<b>Outer dimensions (lid closed / w x d x h/mm)</b>	1,400 x 665 x 1,010
<b>Outer dimensions (lid open / w x d x h/mm)</b>	1,400 x 665 x 1,500
<b>Weight (kg)</b>	249 (251/278/287)

The data in brackets are options.

