

DOUBLE CHAMBER MODEL



SD 1000

Standard equipment

- Cylinder sealing
- Wide double sealing
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Program control with sensor (Perfect)
- Compressed air pressure sealing, external air compressor required
- Robust components and construction
- Stainless steel as well as best metal alloys
- Service program for the pump
- Soft ventilation
- Step / impulse vacuum
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment

Selectable options

- Gas flushing (MAP)
- Cut-off and sealing
- Bigger vacuum pumps
- Voltage variants
- External pump
- Higher lid

Technical data

Chamber size (w x l x h / mm)	1,160 x 1,160 x 150 (280)
Control board	
• Standard	Perfect
• Option	–
Sealing length (mm)	4 x 1,020
Sealing seam	double
Distance x (mm)	(925)
Position of sealing bar	
• Standard	front, back
• Option	–
Pump (cbm/h)	205 (305 / 2 x 305)
Power connection	400V / 3Ph+N+PE / 50Hz
Power from (kW)	6,1 (8,3 / 2 x 8,3)
Max. bag (mm)	1,000 x 1,200
Insert plates	3/chamber
Outer dimensions (lid closed / w x d x h / mm)	2,480 x 1,460 x 1,650 (1,780)
Outer dimensions (lid open / w x d x h / mm)	2,480 x 1,460 x 1,900
Weight (kg)	1,380 (1,390 / 1,570)

The data in brackets are options.

