

VACUBOY

Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Lid locking can be unhooked
- Dynamic end position damping of the lid opening
- Vacuum-moulded chambers, hygienic cleaning
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plate for height adjustment
- Convex plexiglas lid

Selectable options

- Gas flushing (MAP)
- Program control with sensor (Perfect)
- Connection for external extraction (container)
- Anti-slip mat
- Cut-off and sealing
- Voltage variants
- Carts
- ESD-Version
- Stronger sealing transformer

Technical data

Chamber size (w x l x h / mm)	360 x 380 x 140
Control board	
• Standard	Comfort
• Option	Perfect
Sealing length (mm)	1 x 350
Sealing seam	double
Distance x (mm)	340
Position of sealing bar	
• Standard	front
• Option	–
Pump (cbm/h)	10
Power connection	230V/1Ph+N+PE/50Hz
Power from (kW)	0,7
Max. bag (mm)	350 x 400
Insert plates	1
Outer dimensions (lid closed / w x d x h/mm)	410 x 500 x 360
Outer dimensions (lid open / w x d x h/mm)	410 x 500 x 760
Weight (kg)	44



Picture can show options.

fmk-web.de

